



Instruction Handbook for Installation, Operation and Maintenance.













Mineral RO" TECHNOLOGY
Removes Dissolved Impurities
Retains Essential Minerals
Multiple Purification
RO + UV + UF + TDS Control

Kent Deta Hai

Sabse Shudh Paani

















Marketed by: KENT RO SYSTEMS LTD. E-6, 7 & 8, Sector-59, Noida, U.P-201 309, India. E-mail: sales@kent.co.in | Website: www.kent.co.in

Manufactured by: KENT RO SYSTEMS LTD.

1) Khasra No. 93, Village-Bantakhedi, Tehsil-Roorkee, District-Haridwar, Uttarakhand-247 668, India.

2) A-6, Sector-87, Noida-201 305, U.P., India.

For customer complaints, contact our Customer Care Officer at: E-6, 7 & 8, Sector -59, Noida, U.P.-201 309, India. Call: 92-789-12345 E-mail: service@kent.co.in or visit us at www.kent.co.in





Dear Customer,

At the outset, allow us to thank you for your trust in **KENT** water purifiers. We take pride in our reputation for product quality and industry proven performance. We are certain that your decision to own a **KENT Grand Mineral RO**™ water purifier will go a long way towards keeping you and your family in good health. We are confident that you will be satisfied with its performance and that it will serve your need for safer and cleaner drinking water without any compromise.

This guide will help you in getting the best out of your water purifier. Please go through this booklet to familiarise yourself with its operation and maintenance.

You can look forward to years of trouble free service. To ensure that the warranty of your water purifier is effective, it is important that you fill up the enclosed warranty card and mail us the installation report within 15 days of purchase. In case you need any further information, contact your nearest KENT dealer or branch.

Best Wishes,

KENT RO SYSTEMS LTD.


Table of Contents

1.	KENT TECHNOLOGY - A Breakthrough in Water Purification	1
2.	Salient Features	1
3.	Important Instructions	2
4.	Items in the Box	3
5.	Reverse Osmosis Process	3
6.	s. UV Process	
7.	Auto-flushing Systems	3
8.	Water Flow Diagram	4
9.	Electrical Circuit Diagram	4
10.	UV Fail Alarm	5
11.	Filter Change Alarm	5
12.	Computer Controlled Operation	5
13.	Automatic Operation	5
14.	Installation Instructions	6
15.	Recommended Uses of Rejected Water	8
16.	TDS Adjustment	9
17.	Starting-up the Purifier	9
18.	Maintenance	9
19.	Important Safety Instructions	10
20.	Warning	10
21.	Technical Specifications	1′
22.	Testing Information	11

KENT TECHNOLOGY - A Breakthrough in Water Purification*

Presenting the **KENT** Grand Mineral RO[™] Water Purifier. It uses futuristic, state-of-the-art technology to provide purer & healthier drinking water.

At the heart of **KENT** Grand Mineral RO™ Water Purifier is a Reverse Osmosis membrane having capillaries as small as 0.0001 microns that reduces dissolved impurities (salts and heavy metals) and converts hard water to sweet and purer drinking water. **KENT** Grand Mineral RO[™] Water Purifier also allows user to control Total Dissolved Solids (TDS) level of purified water.



KENT is pleased to introduce Save Water Technology™ that helps you save and store water from KENT RO Purifiers as well as from other RO purifiers.

As a part of Save Water Technology, KENT introduces RO Reject Water Storage Tank, which can be purchased separately and then installed and connected to your KENT RO Purifier. This tank stores the rejected water from the purifier, which can be used for washing utensils and mopping the floor. This unique technology helps in high water recovery, thus reducing wastage.

Salient Features of KENT Grand Mineral RO™ Water Purifier

- Double treatment by RO + UV* processes
- High water recovery**
- An eye appealing design
- High Purification efficiency of 20 L/hr.
- Inbuilt TDS Controller that allows adjustment of TDS level of purified water
- Suitable for purification of Brackish/Tap Water / Municipal Corporation Water Supply
- Wall mounted design; best suited for indian homes and offices
- 8 L storage tank with water level indicator
- Fully automatic operation, with auto-on and auto-off function
- Computer controlled operations for enhanced purity and long life

- Filter Change Alarm* to indicate filter replacement time
- UV Fail Alarm* to indicate failure in UV system
- RO Membrane fused inside membrane housing to prevent tampering
- Vertically mounted SMPS for protection from
- Use of push-fit fittings for leakage and maintenance free performance
- ABS construction for corrosion free use
- Inbuilt auto flushing system
- Membrane with high flow


Important Instructions




Avoid exposure to direct sunlight and installation in damp areas.




Make sure that the temperature of water entering the purifier is within 10° C to 40° C.




Make sure that the rejected water pipe is not placed at a level higher from the purifier, otherwise rejected water may flow backwards into the purifier.



water source and the purifier should not be more than 3 meters.



Do not bend or block the reject water pipe.





In case of not using the purifier for more than two days, kindly switch off the power supply and drain the storage tank.

To keep the storage tank clean, it should be drained once in 15 days.



KENT



Use Genuine KENT Spares for optimum performance.



Do not try to service the purifier on your own. Instead, call service technician for help.

^{*}Tested & certified by TUV-SUD South Asia (P) Ltd.


^{**}High water recovery is based on standard testing conditions.



1.	KENT Grand Mineral RO [™] Water Purifier		01 No.
2.	3-Way Connector	:	01 No.
3.	S.S. Ball Valve	:	01 No.
4.	Food Grade Pipe ¼ inch (White)	:	2.5 m
5.	Food Grade Pipe % inch (White)	:	2.5 m
6.	Instruction Manual	:	01 No.
7.	Screws & Plastic Inserts	:	02 Nos. each
8.	Sticker Center Drill	:	01 No.

Reverse Osmosis Process

The Reverse Osmosis process, also known as hyper filtration, is the finest filtration process known till date. The process ensures reduction of particles as small as ions from a solution. Reverse Osmosis uses a semi-permeable membrane to reduce salts from potable / brackish water. In Reverse Osmosis, water pressure applied to the concentrated side forces the process of osmosis into reverse. Under enough pressure, treated water is "squeezed" through the membrane from the concentrated side to the diluted side. Salts dissolved in water as charged ions are repelled by the RO membrane. The




rejected impurities on the concentrated side of the membrane are washed away in a stream of waste water and thus, do not get accumulated as in a traditional filter.

UV Process

The UV light has shorter wavelength (higher energy) than the visible light. It is called ultra-violet because it is just beyond violet light in the light spectrum. Technically, the ultra-violet light is defined to be any wavelength of light, which is shorter than 400 nanometer.

UV rays, which penetrate into the micro-organisms, are absorbed by the DNA of the pathogen in the water. The DNA is altered in such a way that the pathogen cannot reproduce itself. Thus, it is essentially killed and cannot cause infection. This process of DNA modification is called inactivation.



Auto-flushing System

The purpose of the Auto-flushing system is to help prevent scaling or fouling of the RO membrane by providing a rapid rinse which washes away impurities from the membrane's surface and keeps the membrane clean. It offers following benefits.

- Lowers rejected water outflow
- Improves "TDS" rejection rate i.e increases RO membrane efficiency
- Extends the life of RO membrane

3

Warranty Card

Product: KENT GRAND

Product Code: 11076

It is certified that KENT RO Water Purifier purchased as under carries 1 Year Warranty + 3 Years of Free Service*.

(Visit/Service charges will not be charged, however parts if replaced shall be charged)



Serial No	
Purchase Date	Installation Date
Service Provider's	
Name & Address with Stamp	
р	

*To avail this scheme of 3 Years of Free Service, customer must download the KENT Service App at the time of installation. Also future service request must be raised via KENT Service App to avail free service. Terms & Conditions applicable are mentioned overleaf.



Marketed by: KENT RO SYSTEMS LTD.

E-6, 7 & 8, Sector-59, Noida, U.P.-201 309, India. E-mail: service@kent.co.in | Website: www.kent.co.in | Customer Care: 92-789-12345

Terms & Conditions of Warranty

KENT warrants all new products manufactured by it to be free from defects in material and workmanship under normal usage and service from the date of purchase as under:

- 1. It is essential for the customer to download the KENT Service App either on Android or iOS and the customer should lodge a service request via App only.
- 2. In case of emergency during the warranty period, the 15. This warranty agreement excludes all products/ customer may lodge a service request at our Call Centre Ph. 92-789-12345.
- 3. The warranty period commences from the date of installation by the first end-user. During this warranty period of one year, KENT Purifiers or its Authorised Service Provider (ASP) will replace or repair any part of KENT Purifiers, that in the opinion of KENT Purifiers or its ASP, would be defective in operation due to faulty material or workmanship (i.e. manufacturing defects) with the exception of consumables such as Sediment Filter, Carbon Filter and RO/UF Membrane. However, if the RO/UF Membrane gets clogged within first one year and/or if the filters get clogged within first six months, they shall be cleaned / repaired / replaced at no extra 16.
- 4. In addition to this, KENT will also provide free service for a period of next 3 years, wherein Visit/Service charges will not be charged, however parts if replaced shall be 17. Any disagreements and obligations based upon the
- 5. Visit/Service charges will not be charged only for customers residing within 25kms of municipal limits, for other areas additional charges shall be applicable.
- 6. The product's plastic body is not covered under warranty and hence, it must be handled with care to quard against breakage.
- 7. The original purchaser of the unit can avail services under warranty at the point of sale, by producing the damaged part(s) along with the original invoice.
- 8. This warranty is void if the unit is not operated under normal municipal water or well water conditions or is 19. Under no circumstances, the liabilty of KENT Purifiers subjected to the temperature above 40°C.
- 9. Product returned to KENT Purifiers or its ASP for 20. warranty examination must be shipped freight prepaid.
- 10. KENT Purifiers or its ASP shall not be held liable for claims exceeding the cost of repair of the defects in workmanship.
- 11. This warranty agreement shall not be interpreted to 1. render KENT Purifiers or its ASP liable for injuries or damages of any kind-direct, consequential or 2. contingent to persons or property.
- 12. KENT Purifiers or its ASP shall not be held responsible by representative or buyer for failure to abide by any of the obligations of this warranty agreement if such failures are the result of circumstances of Forces 4. Majeures: such as, but not limited to, floods, earthquakes, transportation strikes, labour disputes with outside suppliers or any other conditions beyond the control of KENT Purifiers or its ASP.
- 13. KENT Purifiers or its ASP shall not be held liable for repair or alterations made without prior written approval; for products clogged by suspended matter, precipitates or biological growth; or for failures resulting from the lack of proper maintenance.
- 14. KENT Purifiers or its ASP cannot and shall not be held liable for any sickness or illness due to the consumption of drinking water from any water purifier supplied by

- KENT Purifiers, since KENT Purifiers or its ASP does not have any control over the maintenance and usage of water purifier.
- component parts or damage to any part of this water purifier which, in the opinion of KENT Purifiers or its ASP, have been subjected to misuse; misapplication; negligence; alteration; accident or operation contrary to our instructions, incompatibility with accessories not installed by KENT Purifiers or its ASP, or that have been repaired with component parts other than those manufactured by or obtained from KENT Purifiers or its ASP. Damage caused by freezing, flood, fire or Act of God is not covered by this warranty. In all such cases regular charges will apply. This limited warranty does not include service to diagnose a claimed malfunction in this unit.
- KENT Purifiers reserves the right to alter or improve design and specifications at any time, without any contingent obligations to prospective buyers or owners of the products previously sold.
- purchase of KENT Purifiers products and thereby imposed on KENT Purifiers or its ASP shall be governed by and construed according to the laws of INDIA and subject to the jurisdiction of Delhi Courts only.
- KENT Purifiers or its ASP assumes no warranty liability in connection with this water purifier other than that specified herein. This warranty is in lieu of all other warranties, expressed or implied, including warranties of fitness for a particular purpose. KENT or its ASP does not authorise any person or represent tive to assume for them any other obligations on the sale of this water purifier.
- or its ASP shall exceed the value of the product.
- Under no circumstances are the terms mentioned above negotiable and no employee of KENT Purifiers or its ASP has the authority to supersede them.

Why is it essential to download the KENT Service Application?

- Customer can lodge a service request/complaint anytime (24x7).
- The customer can track/monitor the progressof service request/complaint.
- Complete case history of the services done can be viewed.
- Regular feedback & offer details on the App.



To download the App scan the QR code

Affix Stamp here

309, India U.P.-201 SYSTEMS Noida, **R**0 Sector-59, KENT ∞ ∞ಶ


service@kent.co.in | Website: www.kent.co.in 2-789-1234 Ö Ph.: -mail: ш

Customer's Signature: TDS of Purified Water: Customer's Customer's Address: Customer's Name: Serial No.: Product : KENT GRAND MINERAL RO™ WATER PURIFIER Ph.: Service Provider's Stamp: TDS of Raw Water: Service Provider's Ph.: Service Provider's Address: Service Provider's Name: Installation Date: Invoice Date: Invoice No.:

Installation Report


By signing on this installation report, the customer hereby agrees to the terms & conditions of warranty mentioned on the back side of the warranty card.

Water Flow Diagram



S.NO.	SP - CO.	ITEM DESCRIPTION
1	20035	LOW PRESSURE SWITCH
2	20010	SEDIMENT FILTER
3	20028	SOLENOID VALVE
4	20005	BOOSTER PUMP
5	20009	ACTIVATED CARBON FILTER
6	20003	UF FILTER
7	20034	TDS CONTROL VALVE
8	20529	RO MEMBRANE
9	20020	FLOW RESTRICTOR TUBE
1.0	20541	UV CHAMBER
11	20015	POST CARBON FILTER
12	20058	NON RETURN VALVE
13	20526	WATER STORAGE TANK
14	20030	FLOAT SENSOR

Electrical Circuit Diagram





KENT Grand Mineral RO™ Water Purifier has an in-built feature that sounds an audible alarm if the UV lamp malfunctions. This feature is provided to ensure purity. This UV Fail Alarm will sound as following:

Two short beeps after every two seconds.



In case such an alarm is audible, kindly switch off the purifier and call the service technician for help The purifier will stop its purification process in such a circumstance.

Filter Change Alarm*

KENT Grand Mineral RO[™] has an in-built feature that sounds an audible alarm to indicate replacement time for filters. This alarm will be audible after 700 hrs of use since the last filter change (or since the time of installation). The Filter Change Alarm will sound like following:

4 short beeps after every two seconds; for 30 seconds. The alarm will repeat after every 2 hours of use.



In case such an alarm is audible, please call the service technician and request him to change the filters of the purifier. However, if the filters are not changed within the next 60 hours of operation, the purifier will stop functioning to ensure purity and hygiene. The following alarm will be audible after 60 Hrs. A continuous beep for an infinite time.

In case, such an alarm is audible, kindly switch off the purifier and call the service technician to replace the filters. In such a circumstance, the purifier will not function unless the filters are changed.

Computer Controlled Operation*

To ensure delivery of purer and healthier water, a micro-processor is installed in the purifier that performs the following functions:-

UV Stabilization Delay: To ensure that the UV lamp is pre-heated and is working at its optimum level before it starts disinfecting water, the controller provides a two seconds delay to UV lamp when the purifier is switched on. During this period, only the UV lamp is switched on and other electrical devices of the purifier are switched off.

Purification Delay: To ensure that the idle water lying in the internal pipes and in the UV chamber is disinfected before being passed into the storage tank, the system provides 5 second delay when the purifier is switched on. During this time, the UV lamp kills all micro-organisms that may be in the water inside the UV chamber. After this delay, all other electrical devices such as booster pump and solenoid valve are switched on to start normal purification process.

Audible Alarm: The controller also controls the timing of UV Fail Alarm and the Filter Change Alarm.

Automatic Operation

- storage tank is full
- The purifier does not start when inlet water The purifier does not allow any water rejection in supply pressure is below 0.3 kg/cm²
- The purifier automatically shuts off when the The purifier automatically restarts when water level drops below the maximum
 - absence of electricity or when tank is full
- * Tested & Certified by TUV-SUD South Asia (P) Ltd.

Installation Instructions

KENT Grand

The **KENT** Grand Mineral RO[™] Water Purifier is a product of advanced technology, which ensures safe and clean drinking water. The purifier is easy and convenient to install.


Recommended Site Preparations:

- Single Phase 100-250V AC,50-60 Hz. connection not more than 3m away from the point of installation of purifier
- Raw water supply with ½ inch nipple, not more than 3m away
- Drain for rejected water not more than 3m away
- Space as per dimensions of the purifier
- Wall/plane surface for mounting two screws and holding the machine
- The system and installation must comply with state and local laws and regulations


Specific Instructions:

- **KENT** Grand Mineral RO[™] Water Purifier is a wall mountable purifier. Make sure that it is only mounted on a wall. Avoid installation on wooden and metallic stands
- For optimum performance and minimum inlet pressure required, ensure that the raw water supply tank is at least 10ft above the level at which the purifier is installed
- It is preferable to install the purifier near a sink so that inlet and reject water lines are easily available

Installation Procedure:




- Paste the central drill sticker on wall at (3.6 Feet to 4.0 Feet from the ground) as per your convenience.
- Ensure that sticker is pasted straight on the wall, then drill holes as per the space provided on sticker.
- Now, insert the puff up with the help of a hammer.
- Screw in two 10X50 self-taping screws, 5.11 inches (130 mm) apart horizontally.
- Carefully hang the purifier on the wall with the help of wall-mounting slot holes provided on back side of the purifier. Note: If the wall is not straight or the screws are not properly drilled in an even position, it will damage your purifier. Note: Keep the device away from heat or direct sunlight.



- First fix the SS ball valve (marked as no.4) to the 1/4 inch port of the 3-way connecter (marked as no.2) as shown in figure 2.
- Connect the 3-way connector to the raw water supply (marked as no. 1) as shown in the figure 3. The 3-way connector is fitted in line with the raw water supply.
- The other end of the 3-way connector can be connected to a tap (marked as no.3) as shown in figure 4. or can be plugged off if not required.




- 1. Now connect one end of the white pipe to the SS ball valve and another end to the upper push-fit elbow fitting to the left hand side of the purifier labelled as WATER IN, as shown in fig 1.
- Similarly, connect one end of the white pipe to the lower elbow fitting connector in the tank labelled as REJECT WATER and leave the other end in the drain, as shown in fig 2.



Step-4

Before connecting the power supply, it is important that you perform the following functions:

- 1. Open the SS ball valve (Handle parallel to the ball valve) to start the flow of water into the purifier, as shown in the figure.
- 2. Wait for 2-3 minutes to ensure that the filters are soaked in water.



Step-5

- Connect the power supply.
- 2. Installation is complete.

RO Reject Water Storage Tank (Optional Purchase)

The ideal place for installation is above the sink because rejected water is ideally used for cleaning, utensils or for mopping floors. Every house has used utensils, which can be cleaned first with this water & subsequently with clean water. If you still have extra water left, we recommend you to use it for mopping/cleaning the floor.

Installation Instructions


A. Assembly of tank

Step 01: Open the box and take the storage tank out.	
Step 02: Unscrew and remove the top cover.	
Step 03: Using silicon washer, fix the tap on to the tank.	
Step 04: Attach the fittings on to the holes provided on the side of the tank.	
Step 05: Place the lid back and see to it that it is placed properly.	1

0	Y
Step 06: Screw the lid properly.	
· · · · · · · · · · · · · · · · · · ·	
Step 07: The storage tank is ready for installation.	

B. Wall hanging procedure

- Step 01: Paste the center drill sticker on the wall preferable at 3.6 to 4 feet from the ground or as per convenience.
- Step 02: Ensure that the sticker is pasted straight on the wall. Drill holes as per the markings provided on the sticker.
- Step 03: Using a hammer, insert the puff-up in
- Step 04: Screw two, '10 x 50' sized self-taping screws, 5.5 inches (140 mm) apart horizontally.
- Step 05: Install the tank on wall using screws.
- Step 06: Connect the pipes as shown in the image. Connect 1/4" reject water pipe from the RO to the smaller fitting and 3/8" pipe to the bigger fitting and put the open end into the drain.



Installation is complete.

Note:

- 1. Keep the tank away from direct sunlight or heat.
- 2. If mounted on uneven wall surface or the screws are not properly drilled it could damage the tank.

Warning: The water stored in RO Reject Water Storage Tank is not fit for drinking.

Recommended Uses of Rejected Water

like chlorine, dirt, sand, etc. This rejected water usually goes down the drain but can be used for cleaning utensils & mopping the floor.

Although the rejected water has high concentration We recommend KENT RO Reject Water Storage of salts, it is absolutely clean and free from impurities Tank can be purchased separately to store & use RO reject water.



A unique feature in **KENT** Grand Mineral RO[™] Water Purifier is the TDS control valve, which is not available in any other domestic water purifier till date. This feature allows the user to control the content of natural minerals (TDS) in purified water.

To increase the TDS level, the user can turn the screw

of the valve anti-clockwise; it will result in more mineral content in treated water. To reduce the TDS level, user can turn the screw valve clockwise, it will result in less mineral content in treated water. We recommend the TDS of the purifier to be kept at lowest but not below $50\,\text{mg/l}$.

Starting-up the Purifier

- Switch on the power supply
- Wait till the storage tank fully fills up**
- Switch off the power supply
- Drain the storage tank by opening the drain plug present at the bottom of the storage tank so

as to remove any dust particles present in the pipes and storage tank

- Close the drain plug & switch on the power supply
- The purifier is ready to use

Maintenance

To ensure that the purifier operates at its optimum level, a routine maintenance must be performed. The frequency of the maintenance will greatly depend upon the raw water quality and consumption of treated water.

- Storage tank must be drained once in 2 weeks. To do so, switch off the power supply, open the drain plug at the bottom of the tank & allow the water to drain. Then screw back the plug and switch on the power supply
- Replace sediment, activated carbon & post carbon

when the filter change alarm is audible OR after every 12 months. It is recommended to change the FRT when the filters are replaced

- Replace the RO membrane once in a year
- Replace the UV Lamp once in a year
- If you are not going to use the purifier for a long time (in case you are on a holiday, tour or out of home), make sure that you disconnect the power supply, turn off the raw water supply and drain the storage tank

The reverse osmosis system contains a replaceable treatment component critical for the effective reduction of total dissolved solids and that product water shall be tested periodically to verify that the system is performing properly.

Replacement of spare parts are as under:-

-20010	SP Inline Sediment Filter 8"
-20009	SP Inline Carbon Filter 8"
-20529	SP RO Membrane
-20015	SP Post Carbon Filter (Blue)
-20003	SP Hollow Fibre Membrane (RO)
-20020	SP FRT300/450

^{*} Tested & certified by TUV-SUD South Asia (P) Ltd.

Note: Filters and membrane are consumables. Their replacement time is dependent on the quality of raw water and water consumption. They are not covered under the warranty. However, if a filter chokes within six months and a membrane within a year, it will be cleaned/repaired/replaced free of cost. Changing the filters and system inspection is available on call. The treatment capacity of RO membrane will reduce with time due to clogging of pores of membranes.

"This reverse osmosis system contains a replaceable component critical to the efficiency of the system. Replacement of the reverse osmosis component should be with one of identical specifications as defined by the manufacturer, to ensure the same efficiency and contaminant reduction performance."

Important Safety Instructions

- If the supply cord is damaged, it must be replaced by manufacturer, its service agent or smilarly qualified persons in order to avoid a hazard.
- Children should be supervised to ensure that they do not play with the appliance.
- This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the appliance by a person responsible for their safety.

Warning

- Do not operate the UV-C emitter when it is removed from the appliance enclosure.
- Read the maintenance instructions before opening the appliance.
- The appliance must be disconnected from the supply before replacing the UV-C emitter.

^{**} Tested or certified flushing time - 24hrs.



	•
Product	KENT GRAND
Product Code	11076
Product Generic Name	Water Purifier
Product Colour	White
Applications	Suitable for Purification of Brackish/Tap Water/
	Municipal Corporation Water
Purification Production Rate	20 L/hr.*
Body Material	ABS Food Grade Plastic
Mounting	Wall-mounted
Dimensions(mm)	390 (L) x 255 (W) x 535 (H)
Inlet Water Pressure/Temp (Min.)	0.3 kg/cm² /10°C
Inlet Water Pressure/Temp (Max.)	4 kg/cm² /40°C
Min./Max. Operating pH	6.5-8.0
Filter Cartridge	Sediment, Carbon Block Filter, UF and Post Carbon
Auto Flushing System	Yes
UV Lamp Wattage	11 W
Life of UV Lamp	5000 hrs. of operation
Weight	9.4 kg
Storage Capacity	8 L
Maximum Duty Cycle	100 L/day
Membrane Type	Thin Film Composite RO
Booster Pump Voltage	24 V DC
Total Power Consumption	60 W
Input Power Supply	Single Phase 100-250V AC, 50-60 Hz.□
IP Rating	IPX1

^{*} Treatment capacity tested for tap water having TDS level of 750 ppm at room temperature.

Testing Information

The System has been tested according to IS 10500:2012 (Standards for drinking water as per Bureau of Indian Standards) for reduction of the hazardous substances as listed below.